

# TEK★STAR

LUBRICANTS

TOTAL PROTECTION



TEK 75 S  
SPRAY OIL

# TEK 75 S SPRAY OIL

**TEK 75 S SPRAY OIL** Technical white mineral oil is used for indirect food contact, agricultural applications and processes in the manufacturing of plastics, fibers and other consumer products.

**TEK 75 S SPRAY OIL** is an active carrier for insecticides / pesticides control and horticultural applications. It meets or exceeds the specifications, requirements of FDA 21 CFR 178.3620(c).

**TEK 75 S SPRAY OIL** Este aceite mineral técnico blanco se utiliza para el contacto indirecto de alimentos, aplicaciones agrícolas y los procesos en la fabricación de plásticos, fibras y otros productos de consumo.

**TEK 75 S SPRAY OIL** es un conductor activo para insecticidas / pesticidas y aplicaciones de horticultura. Cumple o excede las especificaciones, requisitos de FDA 21 CFR 178.3620(c).

## TYPICAL PHYSICAL CHARACTERISTICS

Specifications / Especificaciones	Method	75 S
Viscosity, SUS, @ 100°F	D445	76
Viscosity, cSt @ 40°C	D445	13.5
Specific Gravity @ 25°C	D4052	0.8618
Gravity, °API @60°F (15.5°C)	D4052	32.7
Flash Point, COC, °F (°C)	D92	369 (187)
Pour Point, °C(°F)	D5949	-17 (-27)
Color, Saybolt	D156	30
Color, ASTM	D 1500	130.5
FDA 21 CFR 178.3620 (c)	FDA	PASS
Un sulfonated Residue, vol%	D 483	100
Sulfated Ash, wt%	D 482	<0.005
Conradson Carbon Residue, wt%	D 189	0.02
Ramsbottom Carbon Residue, wt%	D 524	0.07
Saturates %	UV Correl.	99
Aromatics %	UV Correl.	0
Polar compounds %	UV Correl.	0



These are typical values subject to stringent industry tolerances. Consult the Material Safety Data Sheet (MSDS) for safety and handling information.

Estos son valores típicos sujetos a las tolerancias estrictas de la Industria. Para el manejo del producto consulte la hoja de seguridad (MSDS)

*Port Consolidated, Inc. expressly disclaims any warranties of merchant ability or fitness, expressed or implied, as to the suitability of 75 S for use in any secondary products including the actual results of its use in any such products. Port Consolidated, Inc. also expressly disclaims the above warranties resulting from the use of this product or any sample of this product in any secondary products.*



Web: [www.tekstarlubricants.com](http://www.tekstarlubricants.com)  
email : [Info@tekstarlubricants.com](mailto:Info@tekstarlubricants.com)  
Product Information: 1-866-tekstar  
MSDS Requests: 1-866-tekstar