

## TEK HYDRAULIC ISO 32, 46, 68

---

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

---

**Product Use:** Hydraulic Oil

**Product Number(s):** TEK20034,

**Synonyms:** TEK Hydraulic ISO 32, 46, 68

**Company Identification :** PORT CONSOLIDATED INC.  
11550 NW 36 AVE  
MIAMI FL 33167-2909  
USA  
[www.portconsolidated.com](http://www.portconsolidated.com)

**Emergency Phone:** (800) 683-5823

**Product Information:** email : [Info@tekstarlubricants.com](mailto:Info@tekstarlubricants.com)  
Web: [www.tekstarlubricants.com](http://www.tekstarlubricants.com)  
Product Information: (866)-tekstar  
MSDS Requests: (866)-tekstar

---

### SECTION 2: COMPOSITION/ INFORMATION ON INGREDIENTS

---

COMPONENTS	CAS NUMBER	AMOUNT
Non-hazardous additive blend in refined oil	Mixture	100 %weight

---

### SECTION 3: HAZARDS IDENTIFICATION

---

#### IMMEDIATE HEALTH EFFECTS

This product is not expected to cause **eye** irritation under normal conditions of use. Symptoms of slight eye irritation may result when direct contact occurs.

Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

No **skin** irritation can be expected from single short-term exposure to this product. Contact with the skin is not expected to cause an allergic skin response. Not expected to be harmful to internal organs if absorbed through the skin. High-Pressure Equipment Information: Accidental high-velocity injection under the skin of materials of this type may result in serious injury. Seek medical attention at once should an accident like this occur. The initial wound at the injection site may not appear to be serious at first; but, if left untreated, could result in disfigurement or amputation of the affected part.

**Ingestion:** Not expected to be harmful if swallowed.

**Inhalation:** Not expected to be harmful if inhaled. Contains a petroleum-based mineral oil. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficulty breathing.

## TEK HYDRAULIC ISO 32, 46, 68

---

### SECTION 4: FIRST AID MEASURES

---

**Eye:** No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

**Skin:** No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

**Ingestion:** No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice.

**Inhalation:** No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

**Note to Physicians:** In an accident involving high-pressure equipment, this product may be injected under the skin. Such an accident may result in a small, sometimes bloodless, puncture wound. However, because of its driving force, material injected into a fingertip can be deposited into the palm of the hand.

Within 24 hours, there is usually a great deal of swelling, discoloration, and intense throbbing pain.

Immediate treatment at a surgical emergency center is recommended..

---

### SECTION 5: FIRE FIGHTING MEASURES

---

Leaks/ruptures in high pressure system using materials of this type can create a fire hazard when in the vicinity of ignition sources.

**FIRE CLASSIFICATION:**

OSHA Classification (29 CFR 1910.1200): Not classified by OSHA as flammable or combustible.

**FLAMMABLE PROPERTIES:**

**Flashpoint:** (Cleveland Open Cup) 171 °C (340 °F) Minimum

**Autoignition:** No data available

**Flammability (Explosive) Limits (% by volume in air):** Lower: Not Applicable Upper: Not Applicable

**Extinguishing Media:** Use dry chemical, foam, carbon dioxide or water fog. Water or foam may cause frothing. Carbon dioxide and inert gas can displace oxygen. Use caution when applying carbon dioxide or inert gas in confined spaces.

**Protection of Fire Fighters:** Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.

---

### SECTION 6: ACCIDENTAL RELEASE MEASURES

---

**Spill Management:** Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

## TEK HYDRAULIC ISO 32, 46, 68

---

**Reporting:** Report spills to local authorities as appropriate or required.

---

### **SECTION 7: HANDLING AND STORAGE**

---

**Precautionary Measures:** DO NOT USE IN HIGH PRESSURE SYSTEMS in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed.

**General Handling Information:** Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

**Static Hazard:** Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. For more information, refer to OSHA Standard 29 CFR 1910.106, 'Flammable and Combustible Liquids', National Fire Protection Association (NFPA 77, 'Recommended Practice on Static Electricity', and/or the American Petroleum Institute (API) Recommended Practice 2003, 'Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents'.

**Container Warnings:** Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioned or disposed of properly.

---

### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

---

#### **GENERAL CONSIDERATIONS:**

Use good personal hygiene practices. Wash hands and other exposed skin areas with plenty of mild soap and water before eating, drinking, smoking, use of toilet facilities, or leaving work. DO NOT use gasoline, kerosene, solvents or harsh abrasives as skin cleaners. Since specific exposure standards/control limits have not been established for this product, the "Oil Mist, Mineral" exposure limits shown below are suggested as minimum control guidelines.

#### **ENGINEERING CONTROLS:**

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of mists and/or vapors below the recommended exposure limits (see below). An eye wash station and safety shower should be located near the work-station.

#### **PERSONAL PROTECTIVE EQUIPMENT**

**Eye/Face Protection:** No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields as a good safety practice.

## TEK HYDRAULIC ISO 32, 46, 68

**Skin Protection:** No special protective clothing is normally required. Where splashing is possible, select protective clothing depending on operations conducted, physical requirements and other substances in the workplace.

Suggested materials for protective gloves include: 4H (PE/EVAL), Nitrile Rubber, Silver Shield, Viton.

**Respiratory Protection:** No respiratory protection is normally required.

If user operations generate an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from the measured concentrations of this material. For air-purifying respirators use a particulate cartridge.

Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

### Occupational Exposure Limits:

Component	Agency	TWA	STEL	Ceiling	Notation
Non-hazardous additive blend in refined oil	ACGIH	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	--	--
Non-hazardous additive blend in refined oil	OSHA Z-1	5 mg/m <sup>3</sup>	--	--	--

Consult local authorities for appropriate values.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**Attention:** The data below are typical values and do not constitute a specification.

**Color:** Clear

**Physical State:** Liquid

**Odor:** Petroleum odor

**pH:** Not Applicable

**Vapor Pressure:** <0.01 mmHg @ 37.8 °C (100 °F)

**Vapor Density (Air = 1):** >1

**Boiling Point:** 315°C (599°F)

**Solubility:** Soluble in hydrocarbons; insoluble in water

Freezing Point: **Not Applicable**

**Specific Gravity:** 0.86 - 0.9 @ 15.6°C (60.1°F) / 15.6°C (60.1°F)

**Density:** 0.86 kg/l - 0.9 kg/l @ 15°C (59°F)

**Viscosity:** 28.8 cSt - 61.2 cSt @ 40°C (104°F) (Min)

## SECTION 10: STABILITY AND REACTIVITY

**Chemical Stability:** This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

**Incompatibility With Other Materials:** May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

**Hazardous Decomposition Products:** None known (None expected)

**Hazardous Polymerization:** Hazardous polymerization will not occur.

## TEK HYDRAULIC ISO 32, 46, 68

---

---

### SECTION 11: TOXICOLOGICAL INFORMATION

---

**Irritation:** The eye irritation hazard is based on evaluation of data for similar materials or product components.

**Skin Irritation:** The skin irritation hazard is based on evaluation of data for similar materials or product components.

**Skin Sensitization:** The skin sensitization hazard is based on evaluation of data for similar materials or product components.

**Acute Dermal Toxicity:** The acute dermal toxicity hazard is based on evaluation of data for similar materials or product components.

**Acute Oral Toxicity:** The acute oral toxicity hazard is based on evaluation of data for similar materials or product components.

**Acute Inhalation Toxicity:** The acute inhalation toxicity hazard is based on evaluation of data for similar materials or product components.

#### **ADDITIONAL TOXICOLOGY INFORMATION:**

This product contains petroleum base oils which may be refined by various processes including severe solvent extraction, severe hydrocracking, or severe hydrotreating. None of the oils requires a cancer warning under the OSHA Hazard Communication Standard (29 CFR 1910.1200). These oils have not been listed in the National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as; carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A), or possibly carcinogenic to humans (Group 2B). These oils have not been classified by the American Conference of Governmental Industrial Hygienists (ACGIH) as: confirmed human carcinogen (A1), suspected human carcinogen (A2), or confirmed animal carcinogen with unknown relevance to humans (A3).

---

### SECTION 12: ECOLOGICAL INFORMATION

---

#### **ECOTOXICITY**

96 hour(s) LC50: >1000 mg/l

48 hour(s) EC50: >1000 mg/l (Daphnia magna)

This material is not expected to be harmful to aquatic organisms.

#### **ENVIRONMENTAL FATE**

No specific ecological data is available for this product. Refer to Section 6 for information regarding accidental release.

---

### SECTION 13: DISPOSAL CONSIDERATIONS

---

Because this product may be mixed with other components, or used in processes that may contaminate it, it is the responsibility of the owner/user to determine at the time of disposal if the product meets RCRA criteria for hazardous waste. Dispose of material and empty containers, liners, and any dilutions, according to local, state, and federal regulations.

## TEK HYDRAULIC ISO 32, 46, 68

---

### SECTION 14: TRANSPORT INFORMATION

---

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

**U.S. Department of Transportation (DOT) 49 - CFR 172.101**

**US DOT Status:** Not regulated by the U.S. Department of Transportation as a hazardous material

**Proper Shipping Name:** Not regulated.

**Hazard Class:** Not regulated.

**Packing Group:** Not applicable.

**UN/NA Number:** Not regulated

**Reportable Quantity:** A Reportable Quantity (RQ) has not been established for this material.

**Emergency Response Guide No.:** Not applicable.

---

### SECTION 15: REGULATORY INFORMATION

---

**EPCRA 311/312 CATEGORIES:**

1. Immediate (Acute) Health Effects: NO
2. Delayed (Chronic) Health Effects: NO
3. Fire Hazard: NO
4. Sudden Release of Pressure Hazard: NO
5. Reactivity Hazard: NO

**REGULATORY LISTS SEARCHED:**

01-1=IARC Group 1	03=EPCRA 313
01-2A=IARC Group 2A	04=CA Proposition 65
01-2B=IARC Group 2B	05=MA RTK
02=NTP Carcinogen	06=NJ RTK
	07=PA RTK

No components of this material were found on the regulatory lists above.

**CHEMICAL INVENTORIES:**

All components comply with the following chemical inventory requirements: AICS (Australia), DSL (Canada), EINECS (European Union), ENCS (Japan), IECSC (China), KECI (Korea), PICCS (Philippines), TSCA (United States).

**NEW JERSEY RTK CLASSIFICATION:**

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows: PETROLEUM OIL (Hydraulic Oil))

**WHMIS CLASSIFICATION:**

This product is not considered a controlled product according to the criteria of the Canadian Controlled Products Regulations..

## TEK HYDRAULIC ISO 32, 46, 68

---

---

### SECTION 16: OTHER INFORMATION

---

#### HMIS and NFPA Hazard Class Information:

**HMIS Hazard Class: Health:** 1 (Slight) **Flammability:** 1 (Slight) **Physical Hazard:** 0 (Least)

**NFPA Hazard Class:Health:** Health: 0 (Least) **Flammability:** 1 (Slight) **Instability:** 0 (Least)

Date of issue: 01/01/2014

#### Disclaimer or Expressed and Implied Warranties:

The above data are based on test, experience, and other information which Port Consolidated, Inc. believes reliable and are supplied for information purposes only. However, some ingredients may have been purchased or obtained from third-party manufacturers. In these instances, Port Consolidated, Inc. in good faith, relies on information provided by those third parties. Since conditions of use are outside our control, PORT CONSOLIDATED INC. DISCLAIMS ANY LIABILITY FOR DAMAGE OR INJURY WHICH RESULTS FROM USE OF THE ABOVE DATA. NOTHING CONTAINED HEREIN SHALL CONSTITUTE A GUARANTEE, WARRANTY (INCLUDING WARRANTY OF MERCHANTABILITY) OR REPRESENTATION (INCLUDING FREEDOM FROM PATENT LIABILITY) BY PORT CONSOLIDATED, INC. WITH RESPECT TO THE DATA, THE MATERIAL DESCRIBED, OR ITS USE FOR ANY SPECIFIC PURPOSE, EVEN IF THAT PURPOSE IS KNOWN TO PORT CONSOLIDATED, INC.

**END OF MATERIAL SAFETY DATA SHEET**